

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>B05B 5/053</b>	<b>A1</b>	(11) International Publication Number: <b>WO 95/32807</b> (43) International Publication Date: 7 December 1995 (07.12.95)
(21) International Application Number: PCT/EP95/02001 (22) International Filing Date: 25 May 1995 (25.05.95) (30) Priority Data: 9410658.0 27 May 1994 (27.05.94) GB (71) Applicant (for all designated States except US): ELEC- TROSOLS LTD. [GB/GB]; Thursley Copse, Farnham Lane, Haslemere, Surrey GU27 1HA (GB). (72) Inventor; and (75) Inventor/Applicant (for US only): COFFEE, Ronald, Alan [GB/GB]; Thursley Copse, Farnham Lane, Haslemere, Surrey GU27 1HA (GB). (74) Agent: RUTTER, Keith; SmithKline Beecham, Corporate In- tellectual Property, SB House, Great West Road, Brentford, Middlesex TW8 9BD (GB).		(81) Designated States: JP, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: DISPENSING DEVICE



(57) Abstract

A device for comminuting a liquid, which comprises at least two electrohydrodynamic comminution means (24) arranged so that in use comminutions of opposing polarity are formed which are substantially admixed after formation, so as to provide a comminution having a residual electrical charge.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

## DISPENSING DEVICE

The invention relates to a dispensing device for comminuting a liquid and the use of such a device, in particular, in medicine.

Known nasal sprays generally produce droplet-sprays by mechanical means. The sprays so produced contain droplets within a broad range of droplet diameters which significantly reduces targeting accuracy and hence accuracy of dosing. The non-uniform nature of the sprays can also be very wasteful of medicament.

Dispensing devices are known which produce a finely divided spray of liquid droplets by electrostatic (more properly referred to as 'electrohydrodynamic') means. The droplet spray in such devices is generated by applying an electric field to a liquid at a spray head or spray edge. The potential of the electric field is sufficiently high to provide comminution of the liquid from the spray head. The droplets produced are electrically charged and thus are prevented from coagulating by mutual repulsion.

We have now discovered that electrohydrodynamic spray technology may be used to deliver charged monodisperse liquid droplets sprays, especially medicament sprays, to the upper respiratory tract and especially to the nasal mucosa, in an efficient and very controllable manner.

We have also discovered that for optimum targeting of the spray in the upper respiratory tract it is desirable to partially remove the electric charge from the droplet sprays produced by electrohydrodynamic comminution devices. To date the principal method used to effect charge removal has required the use of a discharging electrode having a sharp or pointed edge and located downstream from the spray head. This discharging electrode produces a cloud of charged ions from the surrounding air having an opposite electrical charge of equal magnitude to that on the comminuted liquid spray. In use, the ion cloud is attracted towards, collides with and thereby electrically discharges or partially discharges the liquid spray.

European Patent number 0234842 discloses an electrohydrodynamic inhaler wherein the spray of charged droplets is discharged by means of such a discharge electrode. The droplets are discharged in order to facilitate droplet

CONFIRMATION COPY

deposition into the respiratory tract as otherwise the electrically charged droplets would deposit onto the mouth and throat of the user.

A particular problem associated with the use of the sharp discharge electrode is that the highly mobile ion cloud from the discharge electrode often interferes with the comminution of the liquid spray. The inhaler device of EP 0234842 attempts to ameliorate the effects of the ion cloud at the spray head by using a neutral shield electrode located close to the spray head. In addition, the level of control over the partial discharging of the liquid spray, especially the uniformity of charge across the spray cloud, tends to vary within wide limits between zero and the original maximum.

The present invention provides a device which enables the charged spray to be partially discharged in a well controlled manner without affecting the efficiency of the comminution of the liquid spray.

Accordingly, there is provided a device for comminuting a liquid for dispensing to the upper respiratory tract, which comprises at least two electrohydrodynamic comminution means arranged so that in use comminutions of opposing polarity are formed which are substantially admixed after formation, so as to provide a comminution having a residual electrical charge.

The electrohydrodynamic comminution means may be any conventional electrohydrodynamic comminution means, for example those described in the above mentioned patent specifications.

Suitably, each comminution means comprises a comminution site, generally being a surface or edge, from which the liquid comminution is produced.

A preferred comminution surface or edge is provided by a thin capillary tube, a nozzle or a slot defined by two parallel plates. However any comminution surface or edge described in the above mentioned patent specifications may be used suitably adapted for administration to the upper respiratory tract.

The device generally comprises an even number of comminution means but this is not essential, the key factors are that at least two of the comminution means provide comminutions of opposing polarity and that the comminutions produced are arranged to substantially admix.

Suitably, the device comprises 2, 4 or 6 comminution means, however higher numbers can be used as required. An example of a device is that which

has 2 comminution means. An example of a device is that which has 6 comminution means.

Suitably, each comminution means comprises a means for supplying liquid to the comminution site.

Appropriate means for supplying liquid to the comminution site include mechanical, electrical or electronic powered means such as pumps which are capable of providing the required flow rate of liquid to the comminution site.

The comminution means of the invention can be used with a large range of flow rates, but generally operates with flow rates in the range of between 0.1 to 500 $\mu$ L per second, such as 0.5 to 5 $\mu$ L per second, especially for inhaled administration, or 10 to 200 $\mu$ L per second.

A suitable means for supplying the liquid includes a syringe pump or an electrically powered pump as described in EP 0029301.

It will be appreciated from the foregoing that the comminution means generally comprises a comminution site, a means for supplying a liquid to the comminution site and a means for electrically charging the comminution site to an electric potential sufficient to comminute the liquid in use.

Accordingly, in one particular aspect of the invention there is provided a device for comminuting a liquid for dispensing to the upper respiratory tract, which comprises at least two electrohydrodynamic comminution means each comprising a comminution site, a means for supplying a liquid to the comminution site and a means for electrically charging the comminution site to an electric potential sufficient to comminute the liquid in use, wherein the comminution means are arranged so that in use comminutions of opposing polarity are formed which are then substantially admixed so as to provide a comminution having a residual electrical charge.

Suitably, each comminution means comprises a means for electrically charging the said comminution site to a potential sufficient to provide comminution of the liquid, the potential usually being of the order of 1-20 kilovolts.

The means for electrically charging the said comminution site, such as a surface or edge, may be provided by any conventional high voltage generator having the appropriate output, one particularly convenient generator being a piezoelectric generator.

The piezoelectric material for the generator may be chosen from several types, such as barium titanate ceramic, or pvdf polymers, which generate significant high-voltage electric charge displacement upon being pressurized. The choice and capacity may be so chosen as to offer control of the degree of pumping and/or atomization when operated.

The required voltage for use is provided when the piezo-electric generators are squeezed, and again (with opposite polarity) when the piezo-electric generators are released from pressure.

The residual electrical charge on the admixed comminution may be positive or negative charge and of course is less than the positive or negative charge on any of the premixed comminutions. The residual charge on the admixed comminution is arranged so as to optimise targeting of the comminution to the upper respiratory tract.

The residual charge on the admixed comminution may be fixed for any given device or the arrangement may be such that the net residual charge on the admixed comminution may be regulated in a controlled manner. Thus the device of the invention optionally comprises a means for regulating the electrical charge on a comminution produced from any of the comminution means prior to admixture.

Suitable means for regulating the electrical charge on a comminution may be provided by a variety of methods, such as by incorporating a means for regulating the charging means so as to provide variable voltage output and/or a means for regulating the means for supplying a liquid to the comminution site so as to vary the liquid flow rate to the comminution site.

Suitable arrangements of the comminution means which enable the comminutions produced to be admixed includes any arrangement wherein the comminution means are relatively located so as to enable the comminutions to substantially admix. Favourably, the comminution means are arranged so that the comminutions produced are directed to converge into a mixing zone. For example, when the device comprises two comminution means they may be angled towards each other so as to produce comminutions which converge into the mixing zone. Or when the device comprises three or more comminution means, they may be arranged so that the comminutions are directed to converge radially into the mixing zone. Alternatively, the relative location of the comminution means may be arranged such that the mutual attraction of the comminutions produced is

sufficient to allow substantial admixing, for example they may be in a mutually parallel manner.

It is envisaged that a liquid supply means may supply one or more of the comminution means of the invention.

Alternatively, a liquid supply means may supply only one comminution means.

From the foregoing it will be appreciated that it is an aspect of the present invention that comminuted sprays from different liquids may be mixed as required. Such liquids may be capable of providing a new product on admixture or they may comprise components which are so capable. The device may also be used to mix two liquids which are reactive components of a rapid chemical reaction. In each case the mixed droplets may then be applied as a spray, with a charge-to-mass ratio on the droplets that will be the residual after the two opposing charges have been used to coalesce the liquids.

Similarly, the present device may be used to mix components which are incompatible one with the other and which therefore are advantageously admixed at the point of use.

The comminution means of the dispenser is arranged to provide liquid droplets within a diameter range compatible with targeting to the upper respiratory tract, generally being within the range of from 10 to 500 microns in diameter, such as 10 to 200 microns and especially 10 to 25 microns in diameter.

For a given liquid the diameter of the droplets can be controlled by varying the applied voltage and liquid flow rate using routine experimental procedures. Liquids having viscosities within the range of from 1 to 500 centipoise and resistivities in the range of from  $10^2$  -  $10^8$  ohm m can be comminuted by the present device.

Medicaments suitable for delivery by the device include those used for the treatment of disorders of the upper respiratory tract including disorders of the nasal mucosa, in particular congestion and disorders of the upper respiratory tract associated with hay fever. Medicaments suitable for delivery by the device also include those used for the treatment of sore throat.

Particular medicaments include nasal decongestants such as oxymetazoline, xylometazoline, phenylephrine, propylhexadrine, naphazoline and tetrahydrozoline and as appropriate salts thereof such as the hydrochloride salt, and formulations thereof.

When used herein 'a comminution' includes a liquid droplet spray.

When used herein 'medicament' includes proprietary medicines, pharmaceutical medicines and veterinary medicines.

When used herein, unless more specifically defined herein, administration to the upper respiratory tract includes in particular the nasal mucosa.

The liquid medicinal formulations for use in the device of the invention may be formulated according to conventional procedures, such as those disclosed in the US Pharmacopoeia, the European Pharmacopoeia, 2nd Edition, Martindale The Extra Pharmacopoeia, 29th Edition, Pharmaceutical Press and the Veterinary Pharmacopoeia.

The invention may now be described, by way of example, with reference to the accompanying drawings:

Figures 1 to 4 illustrate examples of comminution sites of the device of the invention;

Figure 5 is a plan view illustrating a multi-nozzle comminution site of the device of the invention;

Figure 6 is a schematic drawing illustrating an example of a charging means of the device of the invention;

Figures 7 and 7a are schematic drawings each illustrating an example of a device of the invention;

#### **Comminution sites**

Figure 1 shows a thin-walled capillary tube (1), which may be made of conducting or semiconducting material and which may be electrically connected to a source of high-voltage direct-current, either directly or through the liquid. A single jet (3) is produced from a cusp (2) of liquid, both of which form naturally, according to the voltage and flow rate for a given liquid.

Fig. 2 shows a similar tube (1) used at a lower flow rate and voltage which are adjusted so as to produce multiple cusps (2) and jets (3) issuing from the region of the ends of the thin-walled tube (1).

Fig. 3 shows a conducting or semiconducting cylinder (1) which may have a larger diameter than those shown in figs. 1 and 2. This nozzle has an inner-member, (4) which is approximately coaxial with the outer tube, (1).

Fig. 4 shows a slot nozzle, formed between two parallel plates (2) having conducting, or semiconducting edges electrically connected to a high-voltage direct-current supply, from which the liquid emerges, forming cusps and jets



when the voltage supply and liquid flow rates are suitably adjusted according to the type of liquid being sprayed. For a given jet (and thus droplet) size, and a given liquid, this nozzle may enable a higher flow rate to be achieved than those in which a single cusp and jet are used.

Figure 5, shows one example of an array of six nozzles (1) in a circular pattern, centrally mixing the sprays.

#### **Electrical Charging Means**

An example of this is a piezo electric generator. Figure 6 illustrates a pair of piezoelectric ceramic generators (5) (6) which may be easily squeezed by a cam (7) operated by a trigger-shaped lever (8). The entire assembly may be housed in a strong steel frame, (9), and the piezoelectric pair may be held tight by adjustment screw (10). The voltage terminals (11) are the two live electrodes for connection to the pumps and nozzles, whilst terminal (12) is earthed, say to the steel frame.

When the lever (8) is pulled inward, the two ceramic generators (5) and (6) will produce high voltages upon the terminals (11) placed at the end surfaces, which may be used to activate both the electrokinetic pumps and the nozzles.

Typical values of charge from say a barium titanate ceramic of about 1.0cm length and 1.0 sq cm surface area would be 1.0 or 2.0 microcoulomb per squeeze, of either positive or negative polarity. Upon release of the squeezing pressure, a similar charge will flow in the opposite direction. A typical voltage would be say 5,000 to 10,000 volts. Thus, pumping and atomizing may both be achieved by hand operation of a single pair of piezoelectric generators at appropriate voltages, say 5,000 volts, and sufficient currents, say 2.0 microcoulombs per second (2.0 microamperes).

The piezoelectric material may be chosen from several types, such as barium titanate ceramic, or pvdf polymers, which generate significant high-voltage electric charge displacement upon being pressurized. The choice and capacity may be so chosen as to offer control of the degree of pumping and/or atomization when operated. The liquid flow induction, and the nozzle atomization will occur when the piezo-electric generators are squeezed, and again (with opposite polarity) when the piezo-electric generators are released from pressure. The device is arranged so that when squeezed, and when released, the pumps and nozzles will operate without alteration of flow rate or droplet size. Only polarity will change (reverse) in the two modes of operation arising from

pressure and release of pressure. This will maintain constant flow and droplet generation, and mixing of species and/or charge-to-mass ratio adjustment of the sprays, during the active modes of pressure, and release of pressure.

Some forms of electrical pump are sensitive to polarity so that, when using a piezoelectric source of high voltage such as shown in figure 7, it would be necessary to form a one-way current flow system, say by using simple diode rectifiers as shown in figure 7a. Figure 7a also shows how the nozzle polarities may be kept constant if required, by similarly inserting diodes in and between the connecting lines. Thus figure 7a shows a means of wiring the pumps and nozzles to a pair of piezoelectric generators so that the polarities of the pumps and nozzles remain constant throughout the squeeze and release cycles of the generators.

A schematic representation of the dispenser of the invention is also illustrated in Figure 7 which shows a dispenser of the invention, in which liquid in each of two reservoirs (20) is caused to flow along suitable conduit, say polyethylene tubing (21) into two electrokinetic pumps (22), say by gravity feed. The two piezoelectric generators (23) are then squeezed so that a high voltage charge is induced at the two faces of the piezoelectric materials. These high voltages will then appear at the terminals of the pumps (22), which are electrically connected to the piezoelectric material by wire conductors.

At the same time, these high voltages will appear at the two conducting, or semi-conducting, capillary-tube nozzles (24). Thus, when the two liquids reach the two nozzles, the liquids will emerge from the nozzles as comminuted droplets with electrical charges of opposing polarity. The droplets will then be attracted to each other by electric field forces, and will tend to mix vigorously to give a charged droplet spray for dispensation to the upper respiratory tract.

The value of droplet charge on each of the two streams of droplets may be independently adjusted to produce the optimum residual value for targeting the upper respiratory tract by one or more of several means: the size, shape, and/or materials of the two piezoelectric materials may be set to give differing values of voltage and charge; the two liquid flow rates may also be adjusted, either by suitable design of the two electrokinetic pumps, or by differing values of piezoelectric voltage applied to the two pumps thus directly influencing droplet charge for a given voltage and nozzle design; and the droplet size and charge of the two liquids may be independently adjusted by the formulations of the two liquids, especially by adjustment of the liquid resistivities.

## CLAIMS:

1. A device for comminuting a liquid adapted to dispense the comminution to the upper respiratory tract, which comprises at least two electrohydrodynamic comminution means arranged so that in use comminutions of opposing polarity are formed which are substantially admixed after formation, so as to provide a comminution having a residual electrical charge.
2. A device according to claim 1, wherein the residual electrical charge on the admixed comminution is either positive or negative charge and is arranged so as to optimise targeting of the comminution to the upper respiratory tract.
3. A device according to claim 1 claim 2, wherein the residual charge on the admixed comminution is fixed for any given device.
4. A device according to any one of claims 1 to 3, comprising a means for regulating the electrical charge on a comminution produced from any of the comminution means prior to admixture so that the net residual charge on the admixed comminution is regulated in a controlled manner.
5. A device according to claim 4, wherein the means for regulating the electrical charge on a comminution is provided by means for regulating voltage output and/or by means for regulating liquid flow rate to the comminution site.
6. A device according to any one of claims 1 to 5, comprising an even number of comminution means.
7. A device according to any one of claims 1 to 6, wherein the means for electrically charging the said comminution site is a piezoelectric generator.
8. A device according to any one of claims 1 to 7, wherein the liquid comprises a medicament for the treatment of disorders of the nasal mucosa, in particular congestion and disorders of the upper respiratory tract associated with hay fever and for the treatment of sore throat.

9 A device according to claim 8, wherein the medicament comprises a nasal decongestant such as oxymetazoline, xylometazoline, phenylephrine, propylhexadrine, nephazoline and tetrahydrozoline and as appropriate salts thereof.




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig.5




Fig. 6




Fig. 7




Fig. 7a



## INTERNATIONAL SEARCH REPORT

International Application No  
PCT/EP 95/02001

A. CLASSIFICATION OF SUBJECT MATTER IPC 6 B05B5/053		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols) IPC 6 B05B		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used)		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,X	WO-A-94 12285 (ELECTROSOLS LTD) 9 June 1994	1-6
A	see the whole document ---	8,9
X	US-A-4 508 265 (JIDO) 2 April 1985 see abstract; figure 1 see column 4, paragraph 1 ---	1
P,X	WO-A-94 19042 (BESPAK PLC) 1 September 1994 see abstract see page 2, line 32 - page 3, line 32 see page 9, line 10 - line 29; figure 1 -----	1-5
<input type="checkbox"/> Further documents are listed in the continuation of box C. <input checked="" type="checkbox"/> Patent family members are listed in annex.		
* Special categories of cited documents : "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art. "&" document member of the same patent family		
Date of the actual completion of the international search  8 September 1995		Date of mailing of the international search report  06.10.95
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl, Fax (+ 31-70) 340-3016		Authorized officer  Guastavino, L

# INTERNATIONAL SEARCH REPORT

International application No.

PCT/EP 95/ 02001

## Box III TEXT OF THE ABSTRACT (Continuation of item 5 of the first sheet)

A device for comminuting a liquid, which comprises at least two electrohydrodynamic comminution means (24) arranged so that in use comminutions of opposing polarity are formed which are substantially admixed after formation, so as to provide a comminution having a residual electrical charge.

R

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 95/02001

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO-A-9412285	09-06-94	AU-B- 5570294	22-06-94
		CA-A- 2150692	09-06-94
		CN-A- 1090208	03-08-94
-----			
US-A-4508265	02-04-85	JP-C- 1327513	30-07-86
		JP-A- 57209664	23-12-82
		JP-B- 60057907	17-12-85
-----			
WO-A-9419042	01-09-94	NONE	
-----			

**THIS PAGE BLANK (USPTO)**